



BANDSAW

SAWING FLUIDS

& METALWORKING FLUIDS



PROPERTIES

LENOX PRODUCTS	STARTING WATER HARDNESS RANGE	PRODUCT TYPE % MIN. OIL	CONCENTRATION RANGE	REFRACTO-METER FACTOR	WORKING PH	HIGH PRESSURE FOAM CONTROL
MANUAL APPLICATION						
Protool Lube®	NA, use as is	Synthetic	NA	NA	8.5	NR
SPRAY LUBRICANT						
LENOX LUBE®	NA, use as is	Synthetic	NA	NA	8.6	NR
C/AL™ Lubricant	NA, use as is	Synthetic oil	NA	NA	NA	NR
FLOOD APPLICATION						
BAND-ADE®-SW	5 - 15 dH	Semi, 31%	6-12%	1.7	9	NR
BAND-ADE®-HW	15-25 dH	Semi, 23%	6-12%	1.8	9.1	NR
LENOX® 100CF™-SW	5 - 15 dH	Emulsion, 46%	6-12%	1.1	8.9	YES
LENOX® 100CF™-HW	15-25 dH	Emulsion, 48%	6-12%	1	8.9	YES
SAW MASTER	All	Synthetic, NA	5-20%	3.8	9.1	YES
LENOX® AEROMAX	Demi water	Synthetic, NA	5-10%	2.1	7.8	YES
CLEANER						
Machine Cleaner	All	NA	1-3%	5.3	10.4	NR

METALS / ALLOYS

PRODUCTS	CAST IRON	STEEL	HEAT TREAT STEEL STAINLESS STEEL	ALUMINIUM	CAST ALUMINIUM	HIGH NICKEL ALLOYS	TITANIUM
MANUAL APPLICATION							
Protool Lube®	G	G	G	G	G	G	G
SPRAY LUBRICANT							
LENOX LUBE®	G	G	G	NR	NR	NR	NR
C/AL™ Lubricant	G	G	G	G	G	G	G
FLOOD APPLICATION							
BAND-ADE®-SW BAND-ADE®-HW	B	B	G	B	B	G	G
LENOX® 100CF™-SW LENOX® 100CF™-HW	G	G	G	E	E	B	G
SAW MASTER	G	G	G	NR	NR	NR	NR
LENOX® AEROMAX	NR	G	B	E	E	E	E
CLEANER							
Machine Cleaner	G	G	G	G	G	G	G

NR = NOT RECOMMENDED

G = GOOD

B = BETTER

E = EXCELLENT




LONG BLADE LIFE

Reduced frictional heat and exceptional cooling
for long blade life*



PRODUCTIVITY AND COST SAVINGS

Improved productivity saving costs*



SOLUTIONS AND RESOURCES

Specific solutions for your sawing applications
supported by a highly trained team

*Compared to not using LENOX® band saw sawing fluids and metalworking fluids.